



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Review date: 15/07/2019

## TECHNICAL DATA SHEET DS F.001

### CEBOBREAK

#### Description

Transparent acrylic intermediate primer for interiors, with splitting action to create the craquelle effect .

#### Packaging available

1 litre

#### Coloring

Not expected.

#### Dilution

Not expected.

#### Mixing

Mix the product well before use.

#### Suitable supports

All plaster, lime and civil substrates are suitable . Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

#### Preparation of supports

CeboFix R with a short-haired roller diluted 20-30% by volume with water, in one or two coats until the surface is completely covered.

#### Application

CeboBreak is applied with a brush in one coat, until the surface is completely saturated which, once dry, must be translucent. After at least 4 hours, and in any case within 24 hours of applying CeboBreak , it is necessary to proceed with the application of CeboArt Model to create the Craquelle effect .

Information about the application is contained in videos, folders and catalogs.

#### Technical specifications

Drying: minimum 4 hours maximum 24 hours

Theoretical yield: 10-12 m<sup>2</sup>/Liter

Physical appearance: Transparent liquid

Specific Weight: 1.07 g/cm<sup>3</sup>

pH: 4.5-5.

#### VOC classification (directive 2004/42/EC)

Product category: Primers and fixatives(h)

Maximum permitted limit (2010) for ready-to-use product 30 g/l

CeboBreak contains VOC: 10 g/l

#### Storage

The product has a guaranteed shelf life of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a well-dry and ventilated place, away from sunlight and heat sources.

#### Safety instructions

The product does not require particular environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In case of eye contact, wash your eyes immediately with clean water; if irritation occurs, consult a doctor. Information for the user is contained in the relevant Safety Data Sheet.

This Technical Sheet replaces and cancels all other Sheets relating to the product described, drawn up on a previous date . All the information reported in this Technical Sheet derives from our best experience: however, the Sheet does not imply any acquisition of responsibility on the part of our Company for applications beyond our direct control. Our Technical Office remains always at your disposal to provide further information or clarifications.