

## TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

A050 | **A50 PRIMER PROFESSIONAL**

REPLACES ALL EARLIER VERSIONS

waterproofing  
materials & primers

A<sub>3</sub>

# A50 PRIMER PROFESSIONAL

acrylic water-based undercoat  
for emulsion and acrylic paints

- great coverage & strong adhesion
- surface stabilising
- cost-effective solution



Water-based undercoat for emulsion and acrylic paints. Very good adhesion, toughness and elasticity. Great resistant to alkaline surfaces. Contributes efficiently in the coverage of the finish coat. Provides a uniform mat finish for the finish coat. Quick-drying, allows recoating the same day and seals the surface.

<b>COVERAGE</b>	35±5m <sup>2</sup> /L
<b>FINISH</b>	MATT
<b>THINNING</b>	up to 400% WATER
<b>DRYING TIME</b>	1-2 hours*
<b>RECOATING TIME</b>	1-3 hours*
<b>RECOMMENDED NUMBER OF COATS</b>	1-2 coats
<b>TOOLS</b>	roller, brush or airless paint sprayer

\* Lower temperatures or higher relative humidity will prolong drying and recoating times.

## TECHNICAL CHARACTERISTICS

TYPE	STYRENE ACRYLIC COPOLYMER	
<b>SPECIFIC GRAVITY</b>	TRANSPARENT	1,10 ±0,05g/cm <sup>3</sup>
<b>SOLIDS w/w</b> (ISO 3251-03)		35±3 %
<b>SOLIDS w/v</b> (ISO 3233-98)		32±2 %
<b>VISCOSITY</b> (ASTM D 562-05 @ 25°C)		KU 130±10
<b>APPLICATION VISCOSITY</b> (ASTM D 562-05 @ 25°C)		KU 55±15
<b>pH</b>		8,5±0,5
<b>ACCELERATED AGEING RESISTANCE</b> (ASTM D 1849-03)		10/10 (1 month, 50°C)
<b>APPLICATION TEMPERATURE</b>		min 5°C-max 30°C

## DIRECTIVE 2004/42/CE

EU Limit value for this product in a ready-to-use condition (cat A/g: Primers): 30 g/L (2010). This product contains max: 29 g/L VOC.

PELLACHROM RIZARI AREA-EDESSA-58200, GREECE

T: +30 23810 26868 | +30 23810 91444

www.pellachrom.gr | info@pellachrom.gr

|Page 1 of 2|

PELLACHROM  
DECORATIVE & MARINE COATINGS

## TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

A050 | **A50 PRIMER PROFESSIONAL**

REPLACES ALL EARLIER VERSIONS



### SURFACE PREPARATION

Carefully prepare surface to obtain good results. Surface must be clean, dry and free from loose or flaking material, dust, oils and salts. Putty any surface defects. Prime locally with A50 PRIMER.

- ▶ **New plaster, concrete, brick, cement:**  
Prime with A50 PRIMER thinned 1 (product): 4 (water).
- ▶ **New gypsum board or putty:**  
Prime with A50 PRIMER thinned 1 (product): 4 (water).

### INTENDED USE

■	PLASTER
■	CONCRETE / CEMENT
■	GYSPUM BOARD / PUTTY

### APPLICATION

- ▶ Stir well before use and during application.
- ▶ For best results, surfaces should not be exposed to direct sunlight during paint application.

### USEFUL INFORMATION

- ▶ Allow 30-40 days before coating new plaster or concrete.
- ▶ Do not paint when ambient temperature is below 5°C or if rain is expected.

### PACKAGING

- ▶ Containers of 750ml, 3L and 10L.
- ▶ Create thousands of different colour tints with our COLORTOUCH Tinting System. To ensure product quality, always add COLORTOUCH COLORANTS to Pellachrom Tinting System to create the tint of your choice.

### STORAGE

Two (2) years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-30°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

### CLEAN-UP / DISPOSAL

Keep your tools wet inside the can when not painting. Rub excess paint off your tools on the side of the can after paint application. Clean tools with hot water and soap immediately after use. Do not empty washing liquids into the water table. Always handle empty containers and product carefully. Do not pour leftover product down the drain.

Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

### HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.



**PELLACHROM** RIZARI AREA-EDESSA-58200, GREECE

**T:** +30 23810 26868 | +30 23810 91444

[www.pellachrom.gr](http://www.pellachrom.gr) | [info@pellachrom.gr](mailto:info@pellachrom.gr)

[Page 2 of 2]

**PELLACHROM**  
DECORATIVE & MARINE COATINGS