



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Revision No.1  
Revision date: 15/06/2021

## DATA SHEET DS C.029

### CEBOTIME ACTIVE

#### Description

Indoor acrylic water-based finish, with low dirt grip and high mechanical strength. With a pearly and opaque appearance, easy to apply, it allows to obtain clear, sharp and bright colors, but also very intense colors. The multiple chromatic possibilities make CeboTime Active a versatile and easily usable finish for the enhancement of both classic environments

that modern. CeboTime Active enriched with silver ions, combines the technical and aesthetic qualities of the product with a long-lasting bactericidal and bacteriostatic function. The active protection of silver ions inhibits bacteria that settle on the walls, preventing their proliferation. The product is free from formaldehyde and low in VOC.

The effectiveness of silver ions has been tested against several microorganisms and bacteria such as:

Pseudomonas aeruginosa  
Pseudomonas fluorescens  
Pseudomonas olovorans  
Citrobacter freundii  
Proteus vulgaris  
Escherichia coli,  
Staphylococcus aureus.

#### Packs available

1 Lt - 2,5 Lt - 5 Lt

#### Staining

The product can be coloured with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the colour charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

#### Dilution

Unforeseen.

#### Mixing

Mix the product well before use.

#### Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

#### Media preparation

Apply with short hair roller FondoPlus white diluted to 10% by volume with water, in one or two coats until the bottom is completely covered.

#### Application

CeboTime Active is applied in one or two coats, wait 4-6 hours between the first and second coats. Application information is contained in videos, folders, and catalogs.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.

### Technical specifications

Drying: 4-6 h

Theoretical yield: 7 to 10 m<sup>2</sup>/litre

Physical appearance: Metallic liquid

Specific Weight: 1.15 g/cm<sup>3</sup>

pH: 8.5-9.5

### VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (1)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboTime Active contains VOC: 30 g

### Type of ship IAQ (indoor air quality)



Classification according to the decree of the French Republic N°. 2011-321 of March 2011.

Information on the level of emission of volatile substances into indoor air, which presents a risk of inhalation toxicity, on a class scale ranging from A+ (very low) to C (very high).

### Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

### Safety instructions

The product does not require special environmental or personal protective measures; however, it is advisable to avoid prolonged contact with the skin. In case of eye contact, immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet