



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision n.2
Revision date: 15/07/2019

DATA SHEET DS c.014

CEBOSPARK

Description

Water-based interior finish with a matt appearance that allows, with the addition of CeboGliss or CeboMagic, to create decorations of high aesthetic impact.

Packs available

1 Lt - 2,5 Lt - 5 Lt

Staining

The product can be coloured with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the colour charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

20% by volume with water.

Mixing

Add to the product the chosen additive: CeboGliss or CeboMagic in the dosages indicated in the color charts, mix thoroughly before use. The additive must be used within 6 days.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

Apply with short hair roller FondoPlus white diluted to 10% by volume with water, in one or two coats until the bottom is completely covered.

Application

CeboSpark is applied diluted to 20% by volume with water in two coats, by brush proceeding to cross brushstrokes. Wait 6-8 hours between the first and second hands.

Application information is contained in videos, folders, and catalogs.

Technical specifications

Drying: 6-8 h

Theoretical yield: 7-8 m²/litre

Physical appearance: Liquid, White

Specific Weight: 1.32 g/cm³

pH: 8.5-9.5

VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboSpark contains VOC: 30 g/l

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

This Technical Data Sheet replaces and cancels all the other Data Sheets relating to the product described, drawn up on a previous date. All the information contained in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications beyond our direct control. Our Technical Department is always at your disposal to provide further information or clarifications.

Safety instructions

The product does not require special environmental or personal protective measures; however, it is advisable to avoid prolonged contact with the skin. In case of eye contact, immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.