

## TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

A012 | **INCOVER ECO**

REPLACES ALL EARLIER VERSIONS

paints  
for internal walls



# INCOVER ECO

ecological professional interior  
emulsion paint

- ultimate hiding power & brightness
- ideal for frequent use
- uniform matt finish

INCOVER ECO is an ecological emulsion paint for interior use, certified by the Hellenic Supreme Council for the Award of the Eco-label (ASAOS) according to the criteria of the EU Eco-labelling Board. Ideal for plaster, gypsum board, concrete, brick, etc. During application, the product is odourless. It does not contain ammonia or other dangerous substances as aromatic hydrocarbons, heavy metals or free formaldehyde. An effective and reliable cost solution for professionals. Ultimate hiding power. Suitable for painting and refreshing frequently repainted areas, such as public buildings, ceilings, warehouses. Excellent quality-price ratio.

#### COVERAGE

9±2m<sup>2</sup>/L

#### FINISH

MATT

#### THINNING

10-20% WATER

#### DRYING TIME

1-2 hours\*

#### RECOATING TIME

2-4 hours\*

#### RECOMMENDED NUMBER OF COATS

1-2 coats

#### TOOLS

roller, brush or airless paint sprayer

\* Lower temperatures or higher relative humidity will prolong drying and recoating times.



## TECHNICAL CHARACTERISTICS

TYPE	COPOLYMER VAE	
SPECIFIC GRAVITY	WHITE	1,52 ±0,05g/cm <sup>3</sup>
SOLIDS w/w (ISO 3251-03)	62±2 %	
SOLIDS w/v (ISO 3233-98)	41±3 %	
VISCOSITY (ASTM D 562-05 @ 25°C)	KU 110±10	
APPLICATION VISCOSITY (ASTM D 562-05 @ 25°C)	KU 70±15	
pH	8,5±0,5	
HIDING POWER (ISO 3905)	97%   150µm wet film	
WHITENESS INDEX (ASTM E 313-05)	≥ 88	
YELLOWNESS INDEX (ASTM E 313-05)	≤ 0,5	
GLOSS (60°) (ISO 2813-99)	2,5±1	
GLOSS (85°) (ISO 2813-99)	10±3	
ACCELERATED AGEING RESISTANCE (ASTM D 1849-03)	10/10 (1 month, 50°C)	
APPLICATION TEMPERATURE	min 5°C-max 30°C	

## DIRECTIVE 2004/42/CE

EU Limit value for this product in a ready-to-use condition (cat A/a: Interior matt walls and ceilings: 30 g/L (2010). This product contains max: 10 g/L VOC.

PELLACHROM RIZARI AREA-EDESSA-58200, GREECE

T: +30 23810 26868 | +30 23810 91444

www.pellachrom.gr | info@pellachrom.gr

## TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

A012 | **INCOVER ECO**

REPLACES ALL EARLIER VERSIONS

paints  
for internal walls



### SURFACE PREPARATION

Carefully prepare surface to obtain good results. Surface must be clean, dry and free from loose or flaking material, dust, oils and salts.

- **Surfaces on sound condition:**  
Apply 2 coats of INCOVER ECO.
- **New plaster, concrete, brick, cement:**  
Prime with M51 PRIMER or A50 PRIMER. Apply 2 coats of INCOVER ECO.
- **New gypsum board or putty:**  
Prime with M51 PRIMER or A50 PRIMER. Apply 2 coats of INCOVER ECO.
- **Old water-based or lime paints:**  
Prime with M51 PRIMER thinned up to 50% with water. Apply 2 coats of INCOVER ECO.

### INTENDED USE

■	PLASTER
■	CONCRETE / CEMENT
■	GYSPUM BOARD / PUTTY

### APPLICATION

- Stir well before use and during application.
- Allow newly poured concrete to cure for 30 days, then prime with M51 PRIMER before painting with INCOVER ECO.

### USEFUL INFORMATION

- Allow 30-40 days before coating new plaster or concrete.
- Do not paint when ambient temperature is below 5°C or over 30°C.
- Allow 20-30 days before washing newly painted surfaces.

### PACKAGING

- White. Containers of 750ml, 3L and 9L.
- White tinted to create thousands of different colour tints with our COLORTOUCH Tinting System. To ensure product quality, always add COLORTOUCH COLORANTS to Pellachrom Tinting System to create the tint of your choice.

### STORAGE

Two (2) years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed

place at room temperature between 5-30°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

### CLEAN-UP / DISPOSAL

Keep your tools wet inside the can when not painting. Rub excess paint off your tools on the side of the can after paint application. Clean tools with hot water and soap immediately after use. Do not empty washing liquids into the water table. Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

### HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.



**PELLACHROM** RIZARI AREA-EDESSA-58200, GREECE

**T:** +30 23810 26868 | +30 23810 91444

[www.pellachrom.gr](http://www.pellachrom.gr) | [info@pellachrom.gr](mailto:info@pellachrom.gr)

[Page 2 of 2]

**PELLACHROM**  
DECORATIVE & MARINE COATINGS