



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.2
Revision date: 15/07/219

DATA SHEET DS C.020

CEBOSTYLE

Description

Indoor acrylic water-based finish, washable, opaque, metallic-looking. It allows to obtain surfaces of uniform color but with particular movements due to reflections of light.

Packs available

Silver and Gold: 500 Ml - 1 Lt - 2,5 Lt - 5 Lt

Staining

The product can be coloured with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the colour charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

Unforeseen.

Mixing

Mix the product well before use.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

Apply with short hair roller FondoPlus white diluted to 10% by volume with water, in one or two coats until the base is completely covered.

Application

CeboStyle is applied: in two coats by brush, wait 4-6 hours between the first and the second coat. Application information is contained in videos, folders, and catalogs.

Technical specifications

Drying: 4-6 h

Theoretical yield: 8-10 m²/litre

Physical appearance: Liquid, metallic

Specific Weight: 1.10 g/cm³

pH: 8.5-9.5

VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboStyle contains VOC: 28 g/l

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.

Type of ship IAQ (indoor air quality)



Classification according to the decree of the French Republic N°. 2011-321 of March 2011.

Information on the level of emission of volatile substances into indoor air, which presents a risk of inhalation toxicity, on a class scale ranging from A+ (very low) to C (very high).

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

Safety instructions

The product does not require special environmental or personal protective measures; however, it is advisable to avoid prolonged contact with the skin. In case of eye contact, immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.