

TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

B090 | **DECO GLAZE**

REPLACES ALL EARLIER VERSIONS

decorative
coatings & primers

B

DECO GLAZE

water-based varnish for faux finishes

- finish resistant to frequent washing
- easy to use
- great variety of decorative patterns

Acrylic water-based varnish especially designed to produce a large variety of special decorative effects, since it can be blended with colorants, it can be combined with endless shades and has multiple application techniques. Odourless. Slowly drying offering adequate time for achieving the desired results.



COVERAGE	12±2m ² /L
FINISH	SATIN
THINNING	0-3% WATER
DRYING TIME	1 hour *
RECOATING TIME	4-6 hours *
RECOMMENDED NUMBER OF COATS	1-2 coats
TOOLS	roller, brush or airless paint sprayer

* Lower temperatures or higher relative humidity will prolong drying and recoating times.

TECHNICAL CHARACTERISTICS

TYPE	ACRYLIC DISPERSION	
SPECIFIC GRAVITY	TRANSPARENT	1.02 ±0.05g/cm ³
SOLIDS w/w (ISO 3251-03)	27±2 %	
pH	8.5±0.5	
GLOSS (60°) (ISO 2813-99)	15±2	
GLOSS (85°) (ISO 2813-99)	50±3	
ACCELERATED AGEING RESISTANCE (ASTM D 1849-03)	10/10 (1 month, 50°C)	
APPLICATION TEMPERATURE	min 5°C -max 30°C	

DIRECTIVE 2004/42/CE

EU Limit value for this product in a ready-to-use condition (cat A/L: Decorative effect coatings): 200 g/L (2010). This product contains max: 199 g/L VOC.

PELLACHROM RIZARI AREA-EDESSA-58200, GREECE

T: +30 23810 26868 | +30 23810 91444

www.pellachrom.gr | info@pellachrom.gr

|Page 1 of 2|

PELLACHROM
DECORATIVE & MARINE COATINGS

TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025
B090 | **DECO GLAZE**
REPLACES ALL EARLIER VERSIONS



SURFACE PREPARATION

Carefully prepare surface to obtain good results. Surface must be clean, dry and free from defective or non-cohesive material, dust, oils and salts.

- ▶ **Surfaces on sound condition:**
Prime with AQUAFERM in the shade of your choice. Apply the glossy or satin water-based paint of your choice. Apply 1-2 coats of DECO GLAZE to a dry painted surface.
- ▶ **New plaster, concrete, brick, cement:**
Prime with AQUAFERM or M51 PRIMER. Apply the glossy or satin water-based paint of your choice. Apply 1-2 coats of DECO GLAZE to a dry painted surface.
- ▶ **New gypsum board or putty:**
Prime with AQUAFERM in the shade of your choice. Apply the glossy or satin water-based paint of your choice. Apply 1-2 coats of DECO GLAZE to a dry painted surface.
- ▶ **Old water-based or lime paints:**
Prime with M51 PRIMER thinned up to 50% with water. Apply the glossy or satin water-based paint of your choice. Apply 1-2 coats of DECO GLAZE to the dry painted surface.

INTENDED USE

■	PLASTER
■	CONCRETE / CEMENT
■	GYPSUM BOARD / PUTTY
■	WOOD

APPLICATION

- ▶ Stir well before and during application.
- ▶ Apply DECO GLAZE with a brush or roller in coordination with decorative tools.
- ▶ The surface must be worked per 1m².
- ▶ Join the painted areas together before the surroundings are completely dry.
- ▶ To obtain a more intense result, apply several coats.
- ▶ For concrete, allow a drying period of 30 days before applying M51 PRIMER.

USEFUL INFORMATION

- ▶ On new plaster or concrete surfaces, it is recommended that painting be done after 30-40 days.
- ▶ It is recommended not to apply at temperatures below 5°C and above 30°C.

- ▶ It is recommended that painted surfaces not be washed before 20-30 days have passed since painting.

PACKAGING

- ▶ Containers of 750mL and 375mL.
- ▶ Create thousands of different colour tints with our COLORTOUCH Tinting System.

STORAGE

Two (2) years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-30°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

CLEAN-UP / DISPOSAL

Keep your tools wet inside the can when not painting. Rub excess paint off your tools on the side of the can after paint application. Clean tools with hot water and soap immediately after use. Do not empty washing liquids into the water table. Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.

