TECHNICAL DATA SHEET

EDITION: MARCH 2025 G125 | THINNER 125 REPLACES ALL EARLIER VERSIONS



THINNER 125

special thinner for two- pack epoxy coating

Special thinner for

► ANTIRUST EPOXY



TOOLS

roller, brush or airless spray gun

TECHNICAL CHARACTERISTICS

ТҮРЕ	MIXTURE OF SOLVENTS	
SPECIFIC GRAVITY	TRANSPARENT	0,85 ±0,05g/cm ³
FLASH POINT		25 °C

DIRECTIVE 2004/42/CE

Does not fall into the categories stipulated in Directive 2004/42/EC.

PACKAGING

Available in containers of 375ml, 750ml, 2,5L and 20L.



STORAGE

2 years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-25°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

CLEAN-UP / DISPOSAL

Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.







