

TECHNICAL DATA SHEET

EDITION: MARCH 2025

G135 | **THINNER 135**

REPLACES ALL EARLIER VERSIONS



THINNER 135

thinner for spray gun use

Special thinner for alkyd coatings of our company.

- ▶ PAINTOL
- ▶ METAL-X
- ▶ METALOID
- ▶ MARINE MINIO
- ▶ ANTIRUST
- ▶ ANTIRUST CHASSIS
- ▶ TRAFFIC
- ▶ VELATOURA
- ▶ TROPIKAL

TOOLS

roller, brush or airless spray gun

TECHNICAL CHARACTERISTICS

TYPE	MIXTURE OF SOLVENTS	
SPECIFIC GRAVITY	TRANSPARENT	0,85 ±0,05g/cm ³
FLASH POINT	28 °C	

DIRECTIVE 2004/42/CE

Does not fall into the categories stipulated in Directive 2004/42/EC.

PACKAGING

- ▶ Available in containers of 375ml, 750ml, 2,5L and 20L.



STORAGE

Two (2) years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-30°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

CLEAN-UP / DISPOSAL

Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.



PELLACHROM RIZARI AREA-EDESSA-58200, GREECE

T: +30 23810 26868 | +30 23810 91444

www.pellachrom.gr | info@pellachrom.gr

PELLACHROM
DECORATIVE & MARINE COATINGS